



FERROFLOC

ferrous chloride solution

Precipitant and flocculant for

- Sludge conditioning
- Phosphate elimination
- Bulking sludge abatement
- Hydrogen sulfide elimination
- Industrial effluent treatment

Formula	FeCl ₂
Form	Green solution, about 20 % concentration

Active substance **86 g Fe/kg \triangleq 1.54 mol/kg**
6 g Al/kg \triangleq 0.22 mol/kg

Typical composition	Iron (Fe ²⁺)	8.6	%
	Aluminium (Al)	0.6	%
	Manganese (Mn)	1.4	%
	Magnesium (Mg)	0.6	%
	Insolubles	< 0.003	%

Trace elements	Cd < 0.1 mg/kg*	Ni	110 mg/kg
	Cr 1.4 g/kg	Pb	15 mg/kg
	Cu 1.1 mg/kg	Zn	8 mg/kg
	Hg < 0.01 mg/kg*	AOX	< 2 mg/kg*

* Detection limit

Density	1.36 g/cm ³
---------	------------------------

Delivery	In bulk by rubber-lined road tanker
----------	-------------------------------------

Freezing point	From approx. $-15\text{ }^{\circ}\text{C}$ start of crystallisation* * Targeted dilution with water can prevent crystallisation, so that there are no restrictions in terms of winter operation.
pH value	<1
Consumption of acid capacity ($K_{S4,3}$)	0.21 mmol/100 mg
Concentration for use	Undiluted as delivered or diluted with water to a ratio of 1: 10 at most
Recommended materials	All common plastics except polyamide
Safety	Before using any of our products, please consult our Safety Data Sheets.

The information in this publication is intended to serve as a guide, but is not necessarily complete and is given without warranty. Caution must be exercised to comply with statutory obligations and to avoid infringing rights of third parties.

KRONOS INTERNATIONAL, Inc.

KRONOS ecochem

Peschstr. 5 · 51373 Leverkusen · Germany

Telephone +49 214 356-0 · Fax +49 214 44117

E-mail: kronos.ecochem@kronosww.com

www.kronosecochem.com

© KRONOS 2020

DS2268EN/415EN

FERROFLOC

